

In re application of:

Victor Ivan Chornenky, et al.

Appl. No. Not Yet Assigned

Filed: On a date herewith

For: Device for Delivering Localized X-Ray Radiation and Method of Manufacture

Art Unit:

Examiner:

Atty. Docket: P775 CON 3

## PRELIMINARY AMENDMENT

Assistant Commissioner for Patents Washington, D.C. 20231

Sir:

Prior to examining the application on the merits, please amend the claims as follows: In the Claims:

Please replace claims 31, 34, 37, 38, 39 and 41 as follows:

31. A transmissive device for insertion into a patient's cardiovascular system, comprising: a catheter with a lumen, the catheter having a proximal portion and a distal portion;

an x-ray source at the catheter distal portion, the x-ray source having a vacuum chamber defined by a chamber wall and containing an anode and cathode for generating an electrical field, the vacuum chamber having a diameter less than 3 mm;

an electrically insulating material positioned between the vacuum chamber wall and the anode at joints of the vacuum chamber wall; and

a flexible coaxial cable in the lumen and operably coupled to the x-ray source, the coaxial cable having an outer diameter of three millimeters or less wherein the cable is capable of conducting a voltage greater than or equal to 10 kilovolts without electrical discharge.

- 34. The device of claim 31 wherein the x-ray source requires a voltage of greater than or equal to 10 kilovolts
- 37. The device of claim 31 wherein the device is sized to be inserted into a blood vessel of the body and the device has a maximum diameter of 3.0 millimeters.
- 38. The device of claim 31 wherein the device is sized to be inserted into a blood vessel of the body and the device has a maximum diameter of 2.5 millimeters.
- 39. The device of claim 31 wherein the device is sized to be inserted into a blood vessel of the body and the device has a maximum diameter of 1.5 millimeters.
- 41. A device for insertion into a patient's cardiovascular system, comprising:
  - a catheter with a lumen the catheter having a proximal portion and a distal portion an x-ray source at the catheter distal portion, the x-ray source comprising a composite structure comprising a housing that joins a cathode and an anode, wherein the housing is composed of boron nitride and has a diameter less than 3 mm; and

a flexible coaxial cable in the lumen and operably coupled to the x-ray source.

Dated this 20 day of November 2001.

Respectfully submitted.

Catherine C. Maresh Attorney for Applicant Registration No. 35,268

Medtronic AVE, Inc. 3576 Unocal Place Santa Rosa, CA 95403 Tel. No.: (707) 543-0221

Fax. No.: (707) 543-5420

## **VERSION WITH MARKINGS TO SHOW CHANGES**

31. A transmissive device for insertion into a patient's cardiovascular system, comprising: a catheter with a lumen, the catheter having a proximal portion and a distal portion;

an x-ray source at the catheter distal portion, the x-ray source having a vacuum chamber defined by a chamber wall and containing an anode and cathode for generating an electrical field, the vacuum chamber having a diameter less than 3 mm;

an electrically insulating material positioned between the vacuum chamber wall and the anode at joints of the vacuum chamber wall; and

a flexible coaxial cable in the lumen and operably coupled to the x-ray source, the coaxial cable having an outer diameter of three millimeters or less wherein the cable is capable of conducting a voltage greater than or equal to 10 kilovolts without electrical discharge.

- 34. (Once Amended) The device of claim 31 wherein the [cable is connected at a distal end to a unit requiring] x-ray source requires a voltage of greater than or equal to 10 kilovolts.
- 37. (Once Amended) The device of claim 31 wherein the device is sized to be inserted into [a lumen] a blood vessel of the body and the device has a maximum diameter of 3.0 millimeters.
- 38. (Once Amended) The device of claim 31 wherein the device is sized to be inserted into [a lumen] a blood vessel of the body and the device has a maximum diameter of 2.5 millimeters.
- 39. (Once Amended) The device of claim 31 wherein the device is sized to be inserted into [a lumen] a blood vessel of the body and the device has a maximum diameter of 1.5 millimeters.
- 41. A device for insertion into a patient's cardiovascular system, comprising:

a catheter with a lumen the catheter having a proximal portion and a distal portion an x-ray source at the catheter distal portion, the x-ray source comprising a composite structure comprising a housing that joins a cathode and an anode, wherein the housing is composed of boron nitride and has a diameter less than 3 mm; and a flexible coaxial cable in the lumen and operably coupled to the x-ray source.